



HP 771C 3-pack 775-ml Chromatic Red DesignJet Ink Cartridges

Brand : HP

Product code: B6Y32A

Product name : 771C 3-pack 775-ml Chromatic Red DesignJet Ink Cartridges



- HP 771 3-pack 775-ml Chromatic Red DesignJet Ink Cartridges deliver the high quality your customers expect, even on photo-quality applications. HP Vivid Photo Inks help you respond quickly by providing quality, speed and easy, hassle-free printing.

- Ideal for printing a broad range of output from posters to outstanding photos, maps to fine art, and other indoor applications, including POP displays and backlit signs.

- 3 ink cartridges

771C 3-pack 775-ml Chromatic Red DesignJet Ink Cartridges

HP 771C 3-pack 775-ml Chromatic Red DesignJet Ink Cartridges:

Ideal for printing a broad range of output from posters to outstanding photos, maps to fine art, and other indoor applications, including POP displays and backlit signs.


HP 771 3-pack 775-ml Chromatic Red DesignJet Ink Cartridges deliver the high quality your customers expect, even on photo-quality applications. HP Vivid Photo Inks help you respond quickly by providing quality, speed and easy, hassle-free printing.



Performance		Operational conditions	
Compatibility *	HP DesignJet Z6200 Photo Printer series	Storage temperature (T-T)	-40 - 60 °C
Print technology	Thermal inkjet	Logistics data	
Printing colours	Chromatic red	Master (outer) cases per pallet	51 pc(s)
HP segment	Small medium business	Pallet dimensions (W x D x H)	1016 x 1219 x 569 mm
Country of origin	Singapore	Products per pallet	51 pc(s)
Weight & dimensions		Layers per pallet	3 pc(s)
Width	216 mm	Pallet gross weight	642.3 kg
Depth	289 mm	Pallet gross length	121.9 cm
Height	143 mm	Pallet gross width	101.6 cm
Weight	3 kg	Pallet gross height	56.9 cm
Empty weight	549 g	Quantity per pack	3 pc(s)
Packaging data		Harmonized System (HS) code	84439990
Package width	216 mm	Technical details	
Package depth	289 mm	Box contents	3 ink cartridges
Package height	143 mm	Master (outer) cases per pallet layer	17 pc(s)
Package weight	3.39 kg	Other features	
Operational conditions		UNSPSC-code	441031052
Operating temperature (T-T)	5 - 40 °C		
Operating relative humidity (H-H)	20 - 80%		



0887111301253



887111301253

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.