



HP Designjet 130nr Printer large format printer Colour 2400 x 1200 DPI A1 (594 x 841 mm) Ethernet LAN

Brand : HP

Product family: Designjet

Product code: C7791F

Product name : Designjet 130nr Printer

Designjet 130nr, A1+, 64MB, IEEE 1284, USB 2.0, Fast Ethernet

HP Designjet 130nr Printer. Maximum resolution: 2400 x 1200 DPI, Printing colours: Cyan, Light Cyan, Magenta, Yellow, Maximum duty cycle: 900 pages per month. Total input capacity: 70 sheets, Total output capacity: 50 sheets, Maximum input capacity: 100 sheets. Maximum print size: A1 (594 x 841 mm), Media types supported: Bond and coated paper (coated, heavyweight coated, plain), photo (gloss, high-gloss, semi-gloss,..., ISO A-series sizes (A0...A9): A1, A2, A3, A4. Ethernet interface type: Fast Ethernet, USB connector: USB Type-A. Internal memory: 64 MB, Built-in processor: Impala 2 ASIC, Processor frequency: 16 MHz



Printing		System requirements	
Print head nozzles	304	Compatible operating systems	Microsoft Windows 2000, XP Home, XP Professional, Server 2003, Windows Vista; Mac OS 9.1, Mac OS 9.2, Mac OS X v 10.1.5, Mac OS X v 10.2.2 or higher, Mac OS X v 10.3, 10.4 and 10.5
Colour printing technology	HP Color Layering technology, PhotoRET IV		
Colour *	✔		
Maximum resolution *	2400 x 1200 DPI		
Printing colours *	Cyan, Light Cyan, Magenta, Yellow		
Maximum duty cycle	900 pages per month	Sustainability	
Print head	6 (1 each cyan, magenta, yellow, black, light cyan, light magenta)	Sustainability certificates	ENERGY STAR
Print speed (colour image, draft quality, coated paper)	22.8 m²/hr 245.3 ft²/hr	Weight & dimensions	
Print speed (imperial)	245 ft²/hr	Maximum dimensions (W x D x H)	1050 x 1020 x 220 mm
Print time colour line drawing (draft, A1)	Up to 1.3 min/page	Dimensions (WxDxH)	1050 x 535 x 220 mm
Input & output capacity		Weight	23 kg
Total number of input trays	1	Pallet dimensions (W x D x H)	1200 x 1100 x 2098 mm
Total input capacity	70 sheets	Pallet dimensions (W x D x H) (imperial)	1198.9 x 1099.8 x 2098 mm (47.2 x 43.3 x 82.6")
Total output capacity	50 sheets	Pallet weight (imperial)	244.9 kg (540 lbs)
Maximum input capacity	100 sheets	Product dimensions when open (LxWxD)	104.9 cm (41.3")
Maximum output capacity	50 sheets	Size (imperial)	104.9 cm (41.3")
Paper handling		Weight (imperial)	50.7 lb
Paper handling	70-sheet input tray, single-sheet manual feed, single-sheet rear path for thick media, standard roll feed; 50-sheet output tray	Packaging data	
Duplex print options	None	Package weight	36.8 kg
Maximum print length	15.2 m	Package dimensions (WxDxH)	1192 x 545 x 493 mm
Maximum length of sheet media	1625 mm	Package dimensions (W x D x H)	1191.3 x 546.1 x 495.3 mm (46.9 x 21.5 x 19.5")
Standard media sizes	A1, A1+, A2, A3, A4, B2, B3, B4, envelopes	Package weight (imperial)	36.8 kg (81.2 lbs)
Media types supported	Bond and coated paper (coated, heavyweight coated, plain), photo (gloss, high-gloss, semi-gloss, satin, matte), proofing (high-gloss contract, semi-gloss contract, matte)	Bundled software	HP Designjet drivers for Microsoft Windows and Macintosh
Custom media sizes	Tray 1: 76 x 142 to 457 x 610 mm; manual sheet feed: 110 x 205 to 625 x 1625 mm; rear path: 110 x 205 to 625 x 1625 mm; roll feed: up to 609 mm (by rear path)	Other features	
Maximum print size *	A1 (594 x 841 mm)	Minimum system requirements for Macintosh	iMac G3, G4, G5 dual processor, iBook, PowerBook, eMac; Mac (OS 9.1, OS X v 10.1.5), 128 MB RAM, 100 MB available hard disk space
ISO A-series sizes (A0...A9)	A1, A2, A3, A4	Typefaces	None
		Line accuracy	+/- 0.2 %
		Minimum line width	0.04 mm
		Compatible ink types, supplies	Dye-based HP Viverna inks
		Acoustic power emissions	6.2 B(A)
		Acoustic pressure emissions	50 dB
		Print quality (colour, best quality)	2400 DPI

Paper handling		Other features	
ISO B-series sizes (B0...B9)	B2	Minimum system requirements	Windows 2000 Server (with latest SP), 2000 Professional (with latest SP), XP Professional SP2, Intel Pentium III/AMD Athlon 1.5 GHz or higher, 1 GB RAM per CPU, 40 GB hard drive, 1280 x 768 16-bit color display, DVD-ROM drive Windows 2000 Server (with latest SP), 2000 Professional (with latest SP), XP Professional SP2, Intel Pentium IV 2.5 GHz or higher, 2 GB RAM per printer, 120 GB Serial ATA hard drive, 1280 x 768 16-bit color display, DVD-ROM drive iMac G3, G4, G5 dual processor, iBook, PowerBook, eMac; Mac (OS 9.1, OS X v 10.1.5), 128 MB RAM, 100 MB available hard disk space
Maximum roll length	15.2 m		
Maximum roll diameter	10 cm		
Print margin cut-sheet	5 x 12 x 5 x 5		
Print margin roll	5 mm		
Media weights by paper path	Tray 1: 65 to 150 g/m2; manual single-sheet feed: 65 to 150 g/m2; rear path: up to 300 g/m2; roll feed: 65 to 150 g/m2		
Recommended media weight	Tray 1: 65 - 150; manual single-sheet feed: 65 - 150; rear path: up - 300; roll feed: 65 - 150		
Maximum media width	625 mm		
Media handling	70-sheet input tray, front manual single-sheet feed, rear manual path for thick media, standard roll feed with auto cutter		
Maximum paper trays	1		
Paper handling standard/input	70-sheet input tray, single-sheet manual feed, single-sheet rear path for thick media, standard roll feed	Print quality (black, best quality)	2400 x 1200 DPI
Paper handling standard/output	50-sheet output tray	Electromagnetic compatibility	Compliance for Class B products, Class A when connected to LANs, EU (EMC Directive)
Roll top margin	5 mm	Print speed (colour, normal quality, A4/US Letter)	1.7 ppm
Media sizes supported (imperial)	Letter, legal, tabloid, executive, C, D, C+, D+, envelopes, banners	Printer management	HP Designjet System Maintenance
Media thickness (by paper path)	Tray 1: up to 8 mil; envelopes: up to 15 mil; rear tray: up to 15 mil; manual sheet feed: up to 8 mil; roll media: up to 8 mil	Safety	IEC 950-compliant, EU LVD and EN60950 compliant, Russia VNIIS, Poland ELTEST
Non-printable area roll media (imperial)	0.2 x 0.2 x 0.2 x 0.2 in	Print quality (black, draft quality)	600 DPI
Recommended media weight (imperial)	17 to 56 lb	Driver updates	Latest driver upgrade information available on http://
Ports & interfaces		Ink drop	4 pl
I/O ports	1 parallel, 1 USB 2.0, 1 EIO	Control panel	2 LEDs for status: Power, Attention; 3 keys: Power, Cancel, OK; display area containing information icons
Ethernet interface type	Fast Ethernet	Acoustic power emissions (standby)	54 dB
Ethernet LAN *	✓	JetDirect Compatible Products	✓
USB port *	✓	Line width minimum	0.002 in
USB connector	USB Type-A	Maximum print length (imperial)	50 ft
USB 2.0 ports quantity	1	Maximum media length (imperial)	64"
Parallel ports quantity	1	Media sizes standard (imperial rolls)	3 to 24.6-in wide sheets, up to 24-in rolls
RJ-45 ports quantity	1	Non-printable area (imperial cut-sheet)	0.2 x 0.47 x 0.2 x 0.2 in
Performance		Roll maximum input	1
Internal memory	64 MB	Acoustic pressure emissions (standby)	37 dB(A)
Built-in processor	Impala 2 ASIC	Print resolution (colour, normal quality)	600 x 1200 DPI
Processor frequency	16 MHz	Logistics data	
Power		Products per pallet	8 pc(s)
Power requirements	Input voltage 100 to 240 VAC (± 10%) auto range, 50/60 Hz (± 3 Hz), 2 amp maximum	Pallet gross weight	245 kg
Power consumption (active)	65 W		
Power consumption (typical)	65 W		
Operational conditions			
Recommended operating temperature range (T-T)	15 - 30 °C		
Operating temperature (T-T)	5 - 40 °C		
Operating relative humidity (H-H)	20 - 80%		
Storage temperature (T-T)	-20 - 55 °C		
Operating temperature (T-T)	59 - 86 °F		
Storage relative humidity (H-H)	0 - 95%		

System requirements

Browser supported

Windows: Microsoft Internet Explorer 6.0 and above; Mac OS 9: Netscape 7.0.2 and above, Microsoft Internet Explorer 5.0 and above; Mac OS X: Netscape 7.0.2 and above, Microsoft Internet Explorer (5.2.3 and above, Safari 1.0 and above)



0884420046035



884420046035



0884420359678



884420359678



0884420046097



884420046097



0884420046141



884420046141



0884420046158



884420046158



0884420046165



884420046165



0884420046172



884420046172



0884420046189



884420046189



0884420046196



884420046196



0884420046202



884420046202



0884420046219



884420046219



0884420046042



884420046042



0884420046059



884420046059



0884420046066



884420046066



0884420046073



884420046073



0884420046080



884420046080



0884420046103



884420046103



0884420046110



884420046110



0884420046127



884420046127



0884420046134



884420046134

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.