



HP 83 3-pack 680-ml Yellow UV Cartridges print head Thermal inkjet



Brand : HP

Product code: C5075A

Product name : 83 3-pack 680-ml Yellow UV Cartridges

83 3-pack 680-ml Yellow UV Cartridges

HP 83 3-pack 680-ml Yellow UV Cartridges print head Thermal inkjet:

- High-volume large format supplies users (e. g. retail) who are working with HP Designjet 5000/5500 UV inkjet printing systems. - Professional print service providers (graphic art service bureaus, photo labs, exhibit builders, reproduction houses, sign shops and screen printers), quick printers and copy shops, in-house graphics professionals (advertising agencies, design studios and corporate design departments).
HP 83 3-pack 680-ml Yellow UV Cartridges. Compatibility: HP Designjet 5000, 5500, Print technology: Thermal inkjet, Printing colours: Yellow. Width: 296.9 mm, Depth: 158.8 mm, Height: 223.8 mm. Package width: 296.9 mm, Package depth: 223.8 mm, Package height: 158.8 mm. Master (outer) cases per pallet: 17 pc(s), Products per pallet: 51 pc(s), Layers per pallet: 1 pc(s). Pallet dimensions (W x D x H): 1016 x 1219.2 x 603.25 mm, Stacking number for pallet: 2 pc(s), Pallet size (EU): 1016 x 1219 x 603 mm

Performance		Logistics data	
Compatibility *	HP Designjet 5000, 5500	Master (outer) cases per pallet	17 pc(s)
Print technology	Thermal inkjet	Pallet dimensions (W x D x H)	1016 x 1219.2 x 603.25 mm
Printing colours	Yellow	Products per pallet	51 pc(s)
HP segment	Business	Stacking number for pallet	2 pc(s)
Country of origin	Singapore	Layers per pallet	1 pc(s)
Weight & dimensions		Pallet size (EU)	1016 x 1219 x 603 mm
Width	296.9 mm	Pallet gross weight	206.4 kg
Depth	158.8 mm	Pallet gross length	121.9 cm
Height	223.8 mm	Pallet gross width	101.6 cm
Packaging data		Pallet gross height	60.3 cm
Package width	296.9 mm	Quantity per pack	3 pc(s)
Package depth	223.8 mm	Technical details	
Package height	158.8 mm	Box contents	3 ink cartridges
Package weight	3.52 kg	Master (outer) cases per pallet layer	17 pc(s)
Operational conditions		Other features	
Operating temperature (T-T)	5 - 40 °C	UNSPSC-code	441031052
Storage temperature (T-T)	-40 - 60 °C		



0882780756953




882780756953



0808736596565



808736596565



5400833473005

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.