



Canon imagePROGRAF IPF8000S large format printer Colour 2400 x 1200 DPI A0 (841 x 1189 mm) Ethernet LAN

Brand : Canon

Product family:
imagePROGRAF

Product code: 2161B003

Product name :
ImagePROGRAF IPF8000S

ImagePROGRAF IPF8000S, 44", 2400 x 1200 dpi, 140kg

Canon imagePROGRAF IPF8000S. Maximum resolution: 2400 x 1200 DPI, Page description languages: GARO, Print head: PF-03. Maximum print size: A0 (841 x 1189 mm), ISO A-series sizes (A0...A9): A0, A1, A2, A3, ISO B-series sizes (B0...B9): B0, B2. Ethernet interface type: Fast Ethernet, USB connector: USB Type-A, Supported network protocols: IPX/SPX, SNMP, HTTP, TCP/IP, AppleTalk. Display: LCD, Sound power level (standby): 35 dB, Sound pressure level (printing): 50 dB. Power requirements: 100 - 240 V (50/60 Hz), Power consumption (standby): 6 W, Power consumption (typical): 190 W



Printing		Performance	
Colour *	✓	Sound power level (standby)	35 dB
Maximum resolution *	2400 x 1200 DPI	Sound pressure level (printing)	50 dB
Page description languages *	GARO	Drive device, buffer size	384 MB
Print head	PF-03	Power	
Paper handling		Power requirements	100 - 240 V (50/60 Hz)
Maximum print size *	A0 (841 x 1189 mm)	Power consumption (standby)	6 W
ISO A-series sizes (A0...A9)	A0, A1, A2, A3	Power consumption (typical)	190 W
ISO B-series sizes (B0...B9)	B0, B2	Operational conditions	
Media thickness	0.07 - 0.8 mm	Operating temperature (T-T)	15 - 30 °C
Maximum roll length	19 m	Operating relative humidity (H-H)	10 - 80%
Maximum roll width	111.8 cm	Weight & dimensions	
Maximum roll diameter	15 cm	Dimensions (WxDxH)	1893 x 975 x 1144 mm
Architectural sizes	24", 30", 36"	Weight	140 kg
Ports & interfaces		Packaging data	
Ethernet interface type	Fast Ethernet	Package weight	217 kg
Ethernet LAN *	✓	Package dimensions (WxDxH)	2080 x 1060 x 1242 mm
USB port *	✓	Drivers included	✓
USB connector	USB Type-A	Other features	
USB 2.0 ports quantity	1	Maximum internal memory	80 GB
Supported network protocols	IPX/SPX, SNMP, HTTP, TCP/IP, AppleTalk	Glossy paper	✓
RJ-45 ports quantity	1	Coated paper	✓
Performance		Compliance industry standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Built-in display *	✓		
Display	LCD		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.