



HP 746 DesignJet Printhead

Brand : HP
Product code: P2V25A
Product name : 746 DesignJet Printhead

746 DesignJet Printhead

HP 746 DesignJet Printhead:

Ideal for print service providers, GIS map creators/users, and retailers printing high-quality technical and graphics applications.

There's no need for light color inks using high-definition HP printheads with dual drop technology. True 2400 nozzle-per-inch high-definition nozzle architecture (HDNA) provides twice the nozzle density.^[2]

HP 746 DesignJet Printhead. Compatibility: HP DesignJet Z6 Printer series, HP DesignJet Z9 Printer series, Print technology: Thermal inkjet, OEM code: P2V25A. Width: 28 mm, Depth: 143 mm, Height: 132 mm. Package width: 28 mm, Package depth: 143 mm, Package height: 132 mm. Master (outer) cases per pallet: 80 pc(s), Products per pallet: 1920 pc(s), Layers per pallet: 8 pc(s). Pallet dimensions (W x D x H): 1016 x 1219 x 1318 mm, Pallet dimensions (W x D x H) (imperial): 1016 x 1218.9 x 1318 mm (40 x 48 x 51.9"), Pallet weight (imperial): 255.7 kg (563.7 lbs)



Performance		Logistics data	
Compatibility *	HP DesignJet Z6 Printer series, HP Designjet Z9 Printer series	Master (outer) cases per pallet	80 pc(s)
Print technology	Thermal inkjet	Pallet dimensions (W x D x H)	1016 x 1219 x 1318 mm
OEM code	P2V25A	Products per pallet	1920 pc(s)
Country of origin	Singapore	Layers per pallet	8 pc(s)
Weight & dimensions		Pallet dimensions (W x D x H) (imperial)	1016 x 1218.9 x 1318 mm (40 x 48 x 51.9")
Width	28 mm	Pallet weight (imperial)	255.7 kg (563.7 lbs)
Depth	143 mm	Pallet gross weight	255.7 kg
Height	132 mm	Products per master (outer) case	24 pc(s)
Weight	80 g	Master (outer) case gross weight	2.95 kg
Packaging data		Quantity per pack	1 pc(s)
Package width	28 mm	Harmonized System (HS) code	84439990
Package depth	143 mm	Technical details	
Package height	132 mm	Box contents	Printhead
Package weight	110 g	Total carbon footprint (kg of CO2e)	3.9
Operational conditions		Master (outer) cases per pallet layer	10 pc(s)
Operating temperature (T-T)	5 - 40 °C	Other features	
Operating relative humidity (H-H)	20 - 80%	UNSPSC-code	44103110
Storage temperature (T-T)	-25 - 55 °C		
Storage relative humidity (H-H)	20 - 80%		



0190781037699



190781037699

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.