



HP 886 Latex Printhead print head Thermal inkjet

Brand : HP

Product code: G0Z24A

Product name : 886 Latex Printhead

- Get HP Latex image quality with vivid colors.
- Original HP 886 Latex Printheads enable high-speed quality for both indoor and outdoor applications.
- Revolutionize workflows—no daily manual cleaning of printheads avoids delay.
- Achieve HP Latex image quality and maintain high productivity for both indoor and outdoor applications. Print with ease—and with the environment in mind—with user-replaceable, recyclable^[1] universal HP printheads.
- Print service providers printing large format signage and decorative applications.
- Printhead
886 Latex Printhead

HP 886 Latex Printhead print head Thermal inkjet:

Print service providers printing large format signage and decorative applications. Achieve HP Latex image quality and maintain high productivity for both indoor and outdoor applications. Print with ease—and with the environment in mind—with user-replaceable, recyclable^[1] universal HP printheads.



Performance		Logistics data	
Compatibility *	HP Latex 2700 Printer series, HP Latex R1000 Printer, HP Lates R2000 Printer	Master (outer) cases per pallet	56 pc(s)
Print technology	Thermal inkjet	Pallet dimensions (W x D x H)	1219.2 x 1016 x 1573.28 mm
Country of origin	United States, Singapore	Products per pallet	448 pc(s)
Weight & dimensions		Layers per pallet	7 pc(s)
Width	232 mm	Pallet dimensions (W x D x H) (imperial)	1219.2 x 1016 x 1573.3 mm (48 x 40 x 61.9")
Depth	182 mm	Pallet weight (imperial)	350 kg (771.6 lbs)
Height	64 mm	Pallet gross weight	350 kg
Packaging data		Products per master (outer) case	6 pc(s)
Package width	232 mm	Master (outer) case gross weight	5.73 kg
Package depth	182 mm	Quantity per pack	1 pc(s)
Package height	64 mm	Harmonized System (HS) code	84439990
Package weight	620 g	Technical details	
Operational conditions		Box contents	Printhead
Operating temperature (T-T)	15 - 30 °C	Total carbon footprint (kg of CO2e)	14.7
Operating relative humidity (H-H)	20 - 70%	Master (outer) cases per pallet layer	8 pc(s)
Storage temperature (T-T)	5 - 40 °C	Other features	
Storage relative humidity (H-H)	5 - 95%	UNSPSC-code	44103110



0190781690542



190781690542

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.