



HP 636 3-liter Cyan Stitch Dye Sublimation Ink Cartridge

Brand : HP

Product code: 2LL58A

Product name : 636 3-liter Cyan Stitch Dye Sublimation Ink Cartridge



- Help lower your printing costs with the first dye sub ink formulated to take advantage of HP inkjet technology^[1], that also supports lightweight transfer paper. Recyclable HP Stitch ink cartridges feature water-based, ECO PASSPORT certified inks.^[2]

- Ideal for polyester-based textile application users.

- Ink cartridge

636 3-liter Cyan Stitch Dye Sublimation Ink Cartridge

[HP 636 3-liter Cyan Stitch Dye Sublimation Ink Cartridge:](#)

Ideal for polyester-based textile application users.

Help lower your printing costs with the first dye sub ink formulated to take advantage of HP inkjet technology^[1], that also supports lightweight transfer paper. Recyclable HP Stitch ink cartridges feature water-based, ECO PASSPORT certified inks.^[2]



Performance		Logistics data	
Compatibility *	HP Stitch S500 Printer	Pallet dimensions (W x D x H)	1219.2 x 1016 x 1403 mm
Print technology	Thermal inkjet	Products per pallet	180 pc(s)
Printing colours	Cyan	Layers per pallet	6 pc(s)
HP segment	Business	Pallet dimensions (W x D x H) (imperial)	1219.2 x 1016 x 1403.1 mm (48 x 40 x 55.2")
Country of origin	United States, Singapore	Pallet weight (imperial)	740 kg (1631.4 lbs)
Weight & dimensions		Pallet gross weight	740 kg
Width	192.1 mm	Products per master (outer) case	1 pc(s)
Depth	161.9 mm	Master (outer) case gross weight	4 kg
Height	173 mm	Pallet gross length	101.6 cm
Weight	3.23 kg	Pallet gross width	121.9 cm
Packaging data		Pallet gross height	140.3 cm
Package width	192.1 mm	Quantity per pack	1 pc(s)
Package depth	161.9 mm	Harmonized System (HS) code	84439990
Package height	173 mm	Technical details	
Package weight	6.45 kg	Box contents	Ink cartridge
Operational conditions		Total carbon footprint (kg of CO2e)	7.9
Operating temperature (T-T)	15 - 30 °C	Master (outer) cases per pallet layer	30 pc(s)
Operating relative humidity (H-H)	20 - 80%	Other features	
Storage temperature (T-T)	15 - 30 °C	UNSPSC-code	441031052
Storage relative humidity (H-H)	20 - 80%		
Logistics data			
Master (outer) cases per pallet	180 pc(s)		



0191628916573



191628916573

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.