



HP 618 Magenta and Yellow Stitch Dye Sublimation Printhead print head Thermal inkjet

Brand : HP

Product code: 4UV67A

Product name : 618 Magenta and Yellow Stitch Dye Sublimation Printhead



- Get consistent, like-new image quality and reduce downtime and service costs with recyclable^[2] printheads you can replace yourself. With HP Stitch printheads, you can take full advantage of HP inkjet technology for textile printing.

- polyester-based textile application users.

- Printhead

618 Magenta and Yellow Stitch Dye Sublimation Printhead

HP 618 Magenta and Yellow Stitch Dye Sublimation Printhead print head Thermal inkjet:

polyester-based textile application users.

Get consistent, like-new image quality and reduce downtime and service costs with recyclable^[2] printheads you can replace yourself. With HP Stitch printheads, you can take full advantage of HP inkjet technology for textile printing.



Performance		Logistics data	
Compatibility *	HP Stitch S1000 Printer	Master (outer) cases per pallet	80 pc(s)
Print technology	Thermal inkjet	Pallet dimensions (W x D x H)	1016 x 1219 x 1318 mm
Colour	✓	Products per pallet	1920 pc(s)
Printing colours	Magenta, Yellow	Layers per pallet	8 pc(s)
Country of origin	United States, Singapore	Pallet dimensions (W x D x H) (imperial)	1016 x 1218.9 x 1318 mm (40 x 48 x 51.9")
Weight & dimensions		Pallet weight (imperial)	255.7 kg (563.7 lbs)
Width	28 mm	Pallet gross weight	255.7 kg
Depth	143 mm	Products per master (outer) case	24 pc(s)
Height	132 mm	Master (outer) case gross weight	2.95 kg
Weight	80 g	Quantity per pack	1 pc(s)
Packaging data		Harmonized System (HS) code	84439990
Package width	28 mm	Technical details	
Package depth	143 mm	Box contents	Printhead
Package height	132 mm	Total carbon footprint (kg of CO2e)	14.7
Package weight	110 g	Master (outer) cases per pallet layer	10 pc(s)
Operational conditions		Other features	
Operating temperature (T-T)	15 - 30 °C	UNSPSC-code	44103110
Operating relative humidity (H-H)	20 - 80%		
Storage temperature (T-T)	15 - 30 °C		
Storage relative humidity (H-H)	5 - 95%		



0193015450295



193015450295

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.