



HP 881 Latex Optimizer Printhead

Brand : HP

Product code: CR330A

Product name : 881 Latex Optimizer Printhead

- HP 881 Latex Printheads are low-maintenance, user-replaceable printheads designed to deliver consistent, high-quality results at fast print speeds. Count on high productivity and keep your workflow running smoothly.

- Ideal for large and very large print service providers producing retail advertising, outdoor advertising, event and exhibition displays, vehicle graphics and interior decoration.

- Printhead

881 Latex Optimizer Printhead

[HP 881 Latex Optimizer Printhead:](#)

Ideal for large and very large print service providers producing retail advertising, outdoor advertising, event and exhibition displays, vehicle graphics and interior decoration.

HP 881 Latex Printheads are low-maintenance, user-replaceable printheads designed to deliver consistent, high-quality results at fast print speeds. Count on high productivity and keep your workflow running smoothly.



Performance		Logistics data	
Compatibility *	HP Latex 1500 Printer, HP Latex 3000 Printer, HP Latex 3100 Printer, HP Latex 3500 Printer, HP Latex 3600 Printer, HP Latex 3800 Jumbo Printer	Master (outer) cases per pallet	30 pc(s)
		Pallet dimensions (W x D x H)	1016 x 1219 x 1175 mm
Print technology	Thermal inkjet	Products per pallet	180 pc(s)
OEM code	CR330A	Layers per pallet	5 pc(s)
Country of origin	United States	Pallet size (EU)	1016 x 1219 x 1175 mm
Weight & dimensions		Products per pallet (EU)	180 pc(s)
Width	191 mm	Pallet gross weight	135 kg
Depth	270 mm	Products per master (outer) case	6 pc(s)
Height	95 mm	Master (outer) case gross weight	3.9 kg
Packaging data		Quantity per pack	1 pc(s)
Package width	191 mm	Pallet weight (EU)	135 kg
Package depth	270 mm	Technical details	
Package height	95 mm	Box contents	Printhead
Package weight	570 g	Total carbon footprint (kg of CO2e)	14.7
Operational conditions		Master (outer) cases per pallet layer	6 pc(s)
Operating temperature (T-T)	15 - 30 °C	Other features	
Operating relative humidity (H-H)	20 - 70%	UNSPSC-code	44103110
Storage temperature (T-T)	5 - 40 °C		
Storage relative humidity (H-H)	5 - 95%		



0887758106631



887758106631

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.