



HP Designjet T790 44" large format printer Thermal inkjet Colour 2400 x 1200 DPI A0 (841 x 1189 mm) Ethernet LAN



Brand : HP

Product family: Designjet

Product code: CR649A

Product name : T790 44"

Designjet T790 1118mm ePrinter

HP Designjet T790 44". Print technology: Thermal inkjet, Maximum resolution: 2400 x 1200 DPI, Page description languages: HP-GL/2, HP-RTL, PCL 3, TIFF. Maximum print size: A0 (841 x 1189 mm), Paper tray media types: Bond paper, Coated paper, ISO A-series sizes (A0...A9): A0, A1, A2, A3, A4. Ethernet interface type: Fast Ethernet, USB connector: USB Type-A. Power consumption (standby): 27 W, Power consumption (typical): 120 W, Power consumption (off): 0.1 W. Compatible operating systems: Microsoft Windows 7 Ultimate/Professional/Home Premium, Windows Vista Ultimate/Business/Home...

Printing		Power	
Print technology *	Thermal inkjet	Power consumption (standby)	27 W
Colour *	✓	Power consumption (typical)	120 W
Maximum resolution *	2400 x 1200 DPI	Power consumption (off)	0.1 W
Number of print cartridges *	6	System requirements	
Page description languages *	HP-GL/2, HP-RTL, PCL 3, TIFF	Mac compatibility	✓
Printing colours *	Cyan, Grey, Magenta, Pigment matte black, Yellow	Compatible operating systems	Microsoft Windows 7 Ultimate/Professional/Home Premium, Windows Vista Ultimate/Business/Home Premium; Windows XP (32-bit, 64-bit) Professional/Home, Server 2008 (32-bit, 64-bit), Server 2003 (32-bit, 64-bit); Mac OS X v10.5, v10.6; Citrix XenApp; Citrix XenServer; Linux
Paper handling			
Maximum print size *	A0 (841 x 1189 mm)		
Paper tray media types *	Bond paper, Coated paper		
ISO A-series sizes (A0...A9)	A0, A1, A2, A3, A4		
Media thickness	0.8 mm	Sustainability	
Maximum roll length	91 m	Sustainability certificates	ENERGY STAR
Maximum roll diameter	13.5 cm	Weight & dimensions	
Recommended media weight	60 - 328 g/m²	Dimensions (WxDxH)	1770 x 701 x 1050 mm
Roll paper	✓	Weight	81.6 kg
Ports & interfaces		Other features	
Ethernet interface type	Fast Ethernet	Line accuracy	+/- 0.1%
Ethernet LAN *	✓	Minimum line width	0.06 mm
USB port *	✓	Ink drop	6 pl (C, G, M, pK); 9 pl (mK, Y)
USB connector	USB Type-A	Coated paper	✓
USB 2.0 ports quantity	1	Photo paper	✓
RJ-45 ports quantity	1		



886111274680

885631586303



886111274710

886111404667



886111274727

886111274703



886111274697