



HP 883 5-liter Black Latex Ink Cartridge

Brand : HP **Product code:** G0Z31A

Product name : 883 5-liter Black Latex Ink Cartridge

- Get HP Latex image quality, with 30% wider color gamut.^[1]
 - Finish, laminate, ship, or display right away—prints come off the printer completely dry.
 - Water-based HP Latex Inks—UL ECOLOGO certified, no HAPs/required hazard warning labels, odorless prints.^[4]
 - Achieve amazing colors on flexible substrates with the vibrant HP Latex Ink color gamut. Maintain high productivity with inks that enable fast speeds and come off the printer completely dry. Sharpen your sustainability edge and win.
 - Print service providers printing on flexible media and/or with white ink.
 - Ink cartridge
- 883 5-liter Black Latex Ink Cartridge

HP 883 5-liter Black Latex Ink Cartridge:

Print service providers printing on flexible media and/or with white ink.

Achieve amazing colors on flexible substrates with the vibrant HP Latex Ink color gamut. Maintain high productivity with inks that enable fast speeds and come off the printer completely dry. Sharpen your sustainability edge and win.

Performance		Logistics data	
Compatibility *	HP Latex 2700 Printer	Master (outer) cases per pallet	100 pc(s)
Print technology	Thermal inkjet	Pallet dimensions (W x D x H)	1219 x 1016 x 1401 mm
Printing colours	Black	Products per pallet	100 pc(s)
Country of origin	China, United States, Singapore	Layers per pallet	5 pc(s)
Weight & dimensions		Pallet dimensions (W x D x H) (imperial)	11125.2 x 1016 x 1399.5 mm (438 x 40 x 55.1")
Width	190.5 mm	Pallet gross weight	660.1 kg
Depth	189 mm	Products per master (outer) case	1 pc(s)
Height	229 mm	Quantity per pack	1 pc(s)
Weight	5.98 kg	Harmonized System (HS) code	84439990
Packaging data		Technical details	
Package width	191 mm	Box contents	Ink cartridge
Package depth	189 mm	Total carbon footprint (kg of CO2e)	10.9
Package height	229 mm	Master (outer) cases per pallet layer	20 pc(s)
Package weight	6.25 kg	Other features	
Operational conditions		UNSPSC-code	441031052
Operating temperature (T-T)	15 - 30 °C		
Operating relative humidity (H-H)	20 - 80%		



0195697107252



195697107252



8592978394240

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.